

INDUSTRIAL HD THICK FILM

Introduction

Made for industry, VLS heavy duty thick film coating is the ultimate in di-electric, anti-corrosion, moisture and anti-corrosion protection.

Applications

VLS HD fluid film is a corrosion inhibitor, penetrant, marine lubricant for ferrous and non-ferrous metals. It has excellent adhesion to metal surfaces and resists splash, spray and complete submersion. VLS Industrial HD Thick Film shuts down corrosion and electrolysis and has a dielectric strength of 9800 volts. VLS Industrial HD Thick Film will adhere to materials from -35°C to 55°C and shows no signs of product breakdown or separation up to 120°C.



Performance Data

Physical State:	Thixotropic
Colour:	Red
Odour:	Fresh Scent
Specific Gravity @15.6°C	0.901
Viscosity @25°C, cP:	18,000
Flash Point (COC), °C:	60
Fire Point, °C:	145
Pour Point, °C:	-9
Evaporation Rate:	TBD
Water Solubility:	TBD
Specific Gravity @15.6°C :	0.908 g/cm ³



Available Package Sizes

- 5 gallon pail (20 liters)
- 255 gallon drum (205 liters)

NOTE: Maxon VLS is not a structural or restorative product and should only be used on substrates that are structurally sound.